

ASUS - PRIME B660-PLUS D4 matična ploča



Web cena - 16290.00

web šifra PLO-03400

Karakteristike - PRIME B660-PLUS D4 matična ploča

Brend	
Brend	ASUS
Mreža	
Žična mreža (LAN)	2.5GBase-T (Gigabit)
Model	Realtek
Memorija	
Tip memorije	DDR4
Maksimalna ukupna memorija	128GB
Podržane memorije	2.133Mhz, 3.333Mhz (O.C.), 2.400MHz, 3.600Mhz (O.C.), 3.733Mhz (O.C.), 3.466Mhz (O.C.), 3.400Mhz (O.C.), 3.866Mhz (O.C.), 4.000Mhz (O.C.), 2.666MHz, 4.400Mhz (O.C.), 4.200Mhz (O.C.), 2.933MHz, 2.800MHz, 4.600Mhz (O.C.), 3.000MHz, 4.800Mhz (O.C.), 5.000Mhz (O.C.), 3.200MHz, 5.066Mhz (O.C.)
Ostale osobine	Podrška za Extreme Memory Profile (XMP), Dvokanalni (Dual-channel) režim rada memorije, OptiMem
Memorijski slotovi	4
Fizičke karakteristike	
Dimenzije	305mm x 244mm
Format	ATX
Pakovanje	Full box retail
Stanje	Nekorišćeno
Priključci na zadnjem panelu	
RJ-45 (LAN)	1
Audio	3x 3.5mm
Ukupno USB priključaka	6
VGA D-sub	1
Ukupno USB-C priključaka	1
Broj DisplayPort priključaka	1
Broj HDMI priključaka	1
USB-A priključci	2x USB 10Gbps (3.2 Gen 2), 2x USB 2.0, 1x USB 5Gbps (3.2 Gen 1)
USB-C priključci	1x USB 20Gbps (3.2 Gen 2x2)
Unutrašnji priključci	
Audio	Front panel audio
Ostali priključci	1x COM Port Header, 1 x front panel audio header, 1 x S/PDIF Out header, 1 x Thunderbolt header(s), 1 x 4-pin AIO Pump header, 3 x 4-pin Chassis Fan headers, 1 x 20-3 pin System Panel header with Chassis intrude function, 1 x 4-pin CPU Fan header, 1 x 14-1 pin SPI TPM header, 1 x Clear CMOS header, 3 x Addressable Gen 2 headers, 2 x Aura RGB Strip Headers
Napomena	Za iskorišćavanje određenih internih konektora potrebni su dodatni bracket-i ili priključci na kućištu

Brend	
Mreža	
Memorija	
Fizičke karakteristike	
Priključci na zadnjem panelu	
Unutrašnji priključci	
Audio	
Osnovne karakteristike	
Slotovi	
Skladišni interfejs	
Reklamacioni period	
Zemlja porekla	
Naponski priključci	ATX 24pin, 1x 8 pin 12V Power Connector
USB-A	1 x podrška za 2 USB 5Gbps porta, 2 x podrška za 4 USB 2.0 porta
USB-C	1 x podrška za 1 USB 5Gbps port
Audio	
Broj kanala	8 (7.1)
Model	Realtek
Napomena	PCB izolacija, Audio Shielding
Osnovne karakteristike	
Čipset	Intel B660
Procesorsko ležište (socket)	Intel 1700
Slotovi	
PCI Express x16 slot	1x PCI Express 3.0 (x4 mode), 1x PCI Express 4.0 (x16 mode)
PCI Express x1 slot	2x PCI Express 3.0
Skladišni interfejs	
SATA priključci	SATA III 6Gbps
RAID	RAID 0, RAID 1, RAID 5, RAID 10
SATA priključci (ukupno)	4
Broj M.2 slotova	3
Reklamacioni period	
Reklamacioni period	36 meseci
Zemlja porekla	
Zemlja porekla	Kina